

# Solar Laminate PVL-Series

## Model: PVL-136

# UNI-SOLAR®

- High Temperature and Low Light Performance
- 5-Year Limited Product Warranty
- Limited Power Output Warranty:  
92% at 10 years, 84% at 20 years, 80% at 25 years (of minimum power)
- Quick-Connect Terminals and Adhesive Backing
- Bypass Diodes for Shadow Tolerance

### Performance Characteristics

Rated Power ( $P_{max}$ ): 136 Wp  
Production  $P_{max}$  Tolerance:  $\pm 5\%$

### Construction Characteristics

Dimensions: Length: 5486 mm (216"), Width: 394 mm (15.5"), Depth: 4 mm (0.2"),  
16 mm (0.6") including potted terminal housing assembly

Weight: 7.7 kg (17.0 lbs)

Output Cables: 4 mm<sup>2</sup> (12 AWG) cable with weatherproof DC-rated quick-connect terminals  
560 mm (22") length

Bypass Diodes: Connected across every solar cell

Encapsulation: Durable ETFE high light-transmissive polymer

Adhesive: Ethylene propylene copolymer adhesive sealant with microbial inhibitor

Cell Type: 22 triple junction amorphous silicon solar cells 356 mm x 239 mm  
(14" x 9.4") connected in series

### Qualifications and Safety



UL 1703 Listed by Underwriters Laboratories for electrical and fire safety (Class A Max. Slope 2/12, Class B Max. Slope 3/12, Class C Unlimited Slope fire ratings) for use in systems up to 600 VDC.



IEC 61646 and IEC 61730 certified by TÜV Rheinland for use in systems up to 1000 VDC.


### Laminate Standard Configuration

Photovoltaic laminate with potted terminal housing assembly with output cables and quick-connect terminals on top.

### Application Criteria\*

- Installation temperature between 10 °C - 40 °C (50 °F - 100 °F)
- Maximum roof temperature 85 °C (185 °F)
- Minimum slope: 3° (1/2:12)
- Maximum slope 60° (21:12)
- Approved substrates include certain membrane and metal roofing products. See United Solar for details.

\*Detailed installation requirements are specified in United Solar installation manuals.



Flexible



Lightweight



Durable



No-Glass



Shadow Tolerant



More kWh



High Temp  
Performance



Low Light  
Performance

# Technical Data Sheet



#AA4-3697-04

# Solar Laminate PVL-Series

## Model: PVL-136

# UNI-SOLAR®

IV Curves at various Levels of Irradiance at  
Air Mass 1.5 and 25 °C Cell Temperature



All measurements in mm  
Inches in parentheses  
Tolerances: Length: ± 5 mm (1/4"), Width: ± 3 mm (1/8")

### Electrical Specifications

#### STC

(Standard Test Conditions)  
(1000 W/m<sup>2</sup>, AM 1.5, 25 °C Cell Temperature)

Maximum Power (P<sub>max</sub>): 136 W  
Voltage at P<sub>max</sub> (V<sub>mp</sub>): 33.0 V  
Current at P<sub>max</sub> (I<sub>mp</sub>): 4.13 A  
Short-circuit Current (I<sub>sc</sub>): 5.1 A  
Open-circuit Voltage (V<sub>oc</sub>): 46.2 V  
Maximum Series Fuse Rating: 8 A

#### Temperature Coefficients

(at AM 1.5, 1000 W/m<sup>2</sup> irradiance)

Temperature Coefficient (TC) of I<sub>sc</sub>: 0.001/°K (0.10%/°C)  
Temperature Coefficient (TC) of V<sub>oc</sub>: -0.0038/°K (-0.38%/°C)  
Temperature Coefficient (TC) of P<sub>max</sub>: -0.0021/°K (-0.21%/°C)  
Temperature Coefficient (TC) of I<sub>mp</sub>: 0.001/°K (0.10%/°C)  
Temperature Coefficient (TC) of V<sub>mp</sub>: -0.0031/°K (-0.31%/°C)  
 $y = y_{reference} \cdot [1 + TC \cdot (T - T_{reference})]$

#### Notes:

- During the first 8-10 weeks of operation, electrical output exceeds specified ratings. Power output may be higher by 15%, operating voltage may be higher by 11% and operating current may be higher by 4%.
- Electrical specifications are based on measurements performed at standard test conditions of 1000 W/m<sup>2</sup> irradiance, Air Mass 1.5, and cell temperature of 25 °C after stabilization.
- Actual performance may vary up to 10% from rated power due to low temperature operation, spectral and other related effects. Maximum system open-circuit voltage not to exceed 600 VDC per UL, 1000 VDC per TÜV Rheinland.
- Specifications subject to change without notice.

#### NOCT

(Nominal Operating Cell Temperature)  
(800 W/m<sup>2</sup>, AM 1.5, 1 m/sec. wind)

Maximum Power (P<sub>max</sub>): 105 W  
Voltage at P<sub>max</sub> (V<sub>mp</sub>): 30.8 V  
Current at P<sub>max</sub> (I<sub>mp</sub>): 3.42 A  
Short-circuit Current (I<sub>sc</sub>): 4.1 A  
Open-circuit Voltage (V<sub>oc</sub>): 42.2 V  
NOCT: 46 °C

Your UNI-SOLAR® Distributor:

**Global Headquarters**  
United Solar Ovonic LLC  
2956 Waterview Drive  
Rochester Hills, MI 48309  
Tel: 248.293.0440  
Fax: 248.844.1214  
Toll Free (USA): 1.800.528.0617  
info@uni-solar.com

**European Headquarters**  
United Solar Ovonic  
Europe SAS  
Tour Albert 1er  
65, avenue de Colmar  
92507 Rueil-Malmaison Cedex  
Tel: +33.1.74.70.46.24  
Fax: +33.1.41.39.00.22  
franceinfo@uni-solar.com

**German Office**  
United Solar Ovonic  
Europe GmbH  
Trakehner Strasse 7-9  
60487 Frankfurt/Main  
Tel: +49.69.7137667.0  
Fax: +49.69.7137667.67  
europeinfo@uni-solar.com

**Italian Office**  
United Solar Ovonic  
Europe GmbH  
Via Monte Baldo, 4  
37069 Villafranca (VR)  
Tel: +39.045.8600982  
Fax: +39.045.8617738  
italyinfo@uni-solar.com

**Spanish Office**  
United Solar Ovonic  
Europe GmbH  
C/Jose Ortega y Gasset 25  
28006 Madrid  
Tel: +34 911269051  
Fax: +34 911852670  
spaininfo@uni-solar.com

[www.uni-solar.com](http://www.uni-solar.com)

A subsidiary of Energy  
Conversion Devices, Inc.  
(Nasdaq: ENER)